


# Roller Pumps & Accessories


Delavan Roller pumps offer flexibility in all your spraying applications, and robust enough to deliver 3-24 gallons from your PTO! Delavan roller pumps are the only roller pumps that offers in-field serviceability.














4900C – 9.2 GPM Pump / Cast Iron 5/8" Solid Shaft, Clockwise Rotation

4901C - 9.2 GPM Pump / Cast Iron1/2" Hollow Shaft, Clockwise Rotation

4900DSS – 9.2 GPM Pump / Diamond Stainless Steel 5/8" Solid Shaft, Clockwise Rotation Roundup® Ready

4901DSS – 9.2 GPM Pump / Diamond Stainless Steel 5/8" Solid Shaft, Clockwise Rotation Roundup® Ready

#### Pump:

Type: 4-roller design Max Pressure: 150 PSI

Max Recommended Temperature: 140°F

Port Size: 3/4" FNPT

Mounting: Base Mounted: 5/16" - 18UNC-2B (2 holes)

Weight: 5 lbs

## **Materials of Construction:**

Pump Housing: Cast Iron or Stainless Steel

Rollers: 1/2" Ultra Rollers

Shaft Seals: Viton cartridge type lip seals

Shaft & Rotor:


C: Extra-fine finish 404 SST DSS: Extra-fine finish 416 SST


Bearings: Permanently-lubricated, heavy-duty sealed bearings


PSI	1800 RPM	2200 RPM	2600 RPM	
0	6.3	7.7	9.2	
20	5.8	6.9	8.5	
40	5	6.2	7.9	
60	4.4	5.6	7.5	
80	3.8	5.2	7.2	
100	3.4	4.8	6.8	











6900C - 19.6 GPM Pump/ Cast Iron 6900CR - 19.6 GPM Pump/ Cast Iron Reverse Rotation/Clockwise 6601C – 19.6 GPM Pump/ Cast IronRear Ports (Not Field Serviceable) DKP-6900C - 19.6 GPM Pump/ Cast Iron #90200 Coupler and Torque Arm Kit 6900DSS - 19.6 GPM Pump/ Diamond Stainless Steel 6900DSSR - 19.6 GPM Pump/ Diamond Stainless Steel Reverse Rotation / Clockwise DPK-6900DSS - 19.6 GPM Pump/ Diamond Stainless Steel #90200 Coupler and Torque Arm Kit

#### Pump:

Type: 6-roller design Max Pressure: 300 PSI

Max Recommended Temperature: 140°F

Port Size: 3/4" FNPT 6900: side ports

6901: rear ports – Not field serviceable Mounting: Base Mounted: 5/16" – 18UNC-2B (2 holes) PTO: Use Torque Bar and Chain Weight: 9 lbs

#### **Materials of Construction:**

Pump Housing: Cast Iron or Stainless Steel

Rollers: 1/2" Ultra Rollers

Shaft Seals: Viton cartridge type lip seals Shaft & Rotor: C Extra-fine finish 404 SST


DSS: Extra-fine finish 416 SST


Bearings: Permanently-lubricated, heavy-duty sealed bearings


PSI	540 RPM	1000 RPM	1200 RPM	
0	10.5	19.6	22.8	
20	9.7	19.0	22.0	
40	8.6	18.4	21.3	
60	6.9	16.3	19.7	
80	4.8	13.9	17.9	
100	3.0	11.5	15.8	











7900C - 22.5 GPM Pump/ Cast Iron 7900DSS - 22.5 GPM Pump/ Diamond Stainless Steel

#### Pump:

Type: 7-roller design Max Pressure: 200 PSI

Max Recommended Temperature: 140°F

Port Size: 1" FNPT Mounting:

Base Mounted: 3/8"- 18UNC-2B (2 holes)

PTO: Use Torque Bar and Chain

Weight: 14 lbs

## **Materials of Construction:**

Pump Housing: Cast Iron or Stainless Steel Rollers: 3/4" Ultra Rollers

Shaft Seals: Viton cartridge type lip seals Shaft & Rotor: C Extra-fine finish 404 SST


DSS: Extra-fine finish 416 SST


Bearings: Permanently-lubricated, heavy-duty sealed bearings


PSI	540 RPM	650 RPM	850 RPM			
0	15.2	17.7	22.5			
20	14.5	17.0	21.8			
40	13.6	16.2	21.0			
100	12.0	15.0	20.0			
200	10.0	13.9	18.0			











8900C – 24 GPM Pump/ Cast Iron
8900C R– 24 GPM Pump/ Cast Iron Reverse Rotation/Clockwise
DKP-8900C – 24 GPM Pump/ Cast Iron #90300 Coupler and Torque Arm Kit
8900DSS – 24 GPM Pump/ Diamond Stainless Steel
8900DSSR – 24 GPM Pump/ Diamond Stainless Steel Reverse Rotation / Clockwise
DPK-8900DSS - 24 GPM Pump/ Diamond Stainless Steel
#90300 Coupler and Torque Arm Kit

Pump:

Type: 8-roller design Max Pressure: 300 PSI

Max Recommended Temperature: 140°F

Port Size: 1" FNPT

Mounting:

Base Mounted: 3/8"- 18UNC-2B (2 holes)

PTO: Use Torque Bar and Chain Shaft: 15/16" Solid Shaft

Weight: 14 lbs

#### **Materials of Construction:**

Pump Housing: Cast Iron or Stainless Steel

Rollers: 3/4" Ultra Rollers

Shaft Seals: Viton cartridge type lip seals

Shaft & Rotor:

C: Extra-fine finish 404 SST DSS: Extra-fine finish 416 SST

Bearings: Permanently-lubricated, heavy-duty sealed bearings

PSI	540 RPM	850 RPM	1000 RPM	
0	13.0	20.2	24.0	
20	12.4	19.8	23.2	
40	11.6	19.1	22.4	
100	10.6	18.6	21.8	
200	8.9	15.7	18.0	
300	7.0	14.0	17.1	





## **RollerPRO Accessories**

## **Torque Bar and Chain**

The Torque Bar and Chain is needed to anchor a PTO-mounted pump to keep it from turning with the PTO shaft. Fits all roller pumps Part# 33680

## **RollerPRO Pump Kits**

6-Roller Pump Kit Roller pump with CCW rotations, #90200 coupler, and torque arm kit Part# DPK – 6900C (Cast Iron) Part# DPK – 6900DSS (Diamond Stainless Steel)

8-Roller Pump Kit Roller pump with CCW rotations, #90300 coupler, and torque ar m kit Part# DPK – 8900C (Cast Iron) Part# DPK – 8900DSS (Diamond Stainless Steel)

# **QUICK COUPLERS**

Part#	PTO	Shaft	Tooth	Body	Max RPM	Multi-Speed
90000	1 3/8"	5/8"	9-Tooth	Forged Steel	540 - 1000RPM	•
90100	1 3/8"	15/16"	9-Tooth	Forged Steel	540 - 1000RPM	•
90200	1 3/8"	5/8"	9-Tooth	Die Cast Aluminum	540 - 1000RPM	•
90300	1 3/8"	15/16"	9-Tooth	Die Cast Aluminum	540 - 1000RPM	•
90400	1 3/8"	5/8"	21-Tooth	Forged Steel	1000 PRM	
90500	1 3/8"	15/16"	21-Tooth	Forged Steel	1000 PRM	
90600	1 3/8"	5/8"	6-Tooth	Forged Steel	540 RPM	
90700	1 3/8"	15/16"	6-Tooth	Forged Steel	540 RPM	
90800	1 3/4"	15/16"	20-Tooth	Forged Steel	1000 PRM	













RK-8900 Repair Kit



RK-4900 Repair Kit

# SET SCREW COUPLER (Mild Steel Body & Set Screws)

Part#	Compatible Pumps	Pump	Drive	Max RPM
50101	4400	5/8"	5/8"	2600



# **RollerPRO Pump Repair Kits**

#### **RollerPRO Repair Kits**

Kit contains  $3\overline{/}4$ " ultra rollers, shaft seals seal ring, shaft key and instructions.

4900 Pump – Part# RK-4900 6900 Pump – Part# RK-6900 7900 Pump – Part# RK-7900 8900 Pump – Part# RK-8900

## **Competitive Pump Repair Kits**

Ace, Hypro, TSC, Century, and Teel Pumps. Kit includes 11/16" diameter roller and Viton seals.

6 Roller Kit – Part# 18756 8 Roller Kit – Part# 18768

#### **Old Style Delavan Roller Pump Repair Kits**

Kit contains rollers, shaft seals, 0-rings and instructions

66-3110 Pump – Part# 25227 77-3110 Pump – Part# 25228 77-4111 Pump – Part# 25228 77-311 Pump – Part# 25228 77-410 Pump – Part# 25228

## **Universal Roller Pump Repair Kits**

Kit contains 11/16" ultra rollers, shaft seals, O-rings, and instructions.\*Repairs Delavan and Hypro Roller Pumps

4400 Pump – Part# 44-4000RK 5500 Pump – Part# 55-1700RK 6600 Pump – Part# 66-6500RK 7000 Pump – Part# 77-7700RK 8800 Pump – Part# 88-7560RK